


YAKIT VE YAĞ HORTUMLARI ARA TAKVİYELİ FUEL AND OIL HOSES INNER REINFORCED



YAPISI

Alt kat : ECO Kauçuk
Takviye : Tekstil Örgü
Üst kat : ECO Kauçuk
Normlar : ISO 4639-2/SAE J30 R7
DIN 73379-2A/ EN ISO 1307

ÖZELLİKLER

Özellikler : - 40 °C / 125 °C
Max. Sıcaklık : + 150°C
Ozon, ısı, yağ, ve atmosferik şartlara
extra dayanıklılık sağlar, alçak yakıt
geçirgenliği,yüksek ısı direnci ve esneklik

UYGULAMA ALANLARI

Yakıt ve yağ, dizel, glikol
ve mineral esaslı sıvıların
transferinde kullanılır

CONSTRUCTION

Inner Tube : ECO Rubber
Reinforcement : Textile Braiding
Cover : ECO Rubber
Norms : ISO 4639-2/SAE J30R7
DIN 73379-2A/ EN ISO 1307

FEATURES

Özellikler : - 40 °C / 125 °C
Peak Temperature : + 150°C
Good resistance against ozone,heat
oil, ageing and weathering. Low fuel
permeability, high heat resistance,high flexibility

APPLICATION

Used for transferring fuel
and oil, diesel, liquids on
mineral and glycol base

İç Çap ID Ø (mm)	Çap Ø (Inch)	Dış Çap OD Ø (mm)	Et Kalınlığı Wall thickness (mm)	Bükme Radüsü Bending Radius (mm)	Çalışma Basıncı Working Pressure (bar)	Patlatma Basıncı Bursting Pressure (bar)	Ambalaj Packing (mt)
3,0	7/64"	8,0	2,5	45	10bar	30bar	25 mt
3,5	1/8"	9,5	3,0	45	10bar	30bar	25 mt
4,0	5/32"	10,0	3,0	50	10bar	30bar	25 mt
4,5	3/16"	10,5	3,0	50	10bar	30bar	25 mt
5,0	3/16"	11,0	3,0	55	10bar	30bar	25 mt
5,3	7/32"	11,3	3,0	60	10bar	30bar	25 mt
5,5	7/32"	11,5	3,0	60	10bar	30bar	25 mt
6,0	¼"	12,0	3,0	70	10bar	30bar	25 mt
7,0	9/32"	13,0	3,0	70	10bar	30bar	25 mt
7,3	9/32"	13,3	3,0	70	10bar	30bar	25 mt
7,5	19/64"	13,5	3,0	70	10bar	30bar	25 mt
8,0	5/16"	14,0	3,0	80	10bar	30bar	25 mt
9,0	23/64"	15,0	3,0	80	10bar	30bar	25 mt
9,3	23/64"	15,3	3,0	80	10bar	30bar	25 mt
9,3	23/64"	16,3	3,5	80	10bar	30bar	25 mt
10,0	3/8"	17,0	3,5	80	10bar	30bar	25 mt
11,0	7/16"	18,0	3,5	80	10bar	30bar	25 mt
12,0	½"	19,0	3,5	100	10bar	30bar	25 mt
13,0	½"	23,0	5,0	100	10bar	30bar	25 mt
16,0	5/8"	24,0	4,0	125	10bar	30bar	25 mt
19,0	¾"	27,0	4,0	190	10bar	30bar	25 mt

NOT : Diğer ölçü,markalama ve ambalaj gibi ürün özellikleri müşterinin isteği üzerine değişiklik gösterebilir.

NOTE : Other dimensions,marking and packaging vary upon customer's request