


SU HORTUMLARI TAKVİYESİZ WATER HOSES WITHOUT REINFORCEMENT



YAPISI

Alt kat : EPDM Kauçuk
Takviye : -
Üst kat : -
Normlar : DIN 73411 TİP C

ÖZELLİKLER

 : - 40°C / 120 °C
Max. Sıcaklık : + 150°C


UYGULAMA ALANLARI

Sıcak-soğuk su, buhar ve sıvı soğutma sistemleri

CONSTRUCTION

Inner Tube : EPDM Rubber
Reinforcement : -
Cover : -
Norms : DIN 73411 TYPE C

FEATURES

 : - 40 °C / 120 °C
Peak Temperature : + 150°C

APPLICATION

Hot and cold water, steam, liquid cooling system

İç Çap ID Ø (mm)	Çap Ø (Inch)	Dış Çap OD Ø (mm)	Et Kalınlığı Wall thickness (mm)	Bükme Radüsü Bending Radius (mm)	Çalışma Basıncı Working Pressure (bar)	Patlatma Basıncı Bursting Pressure (bar)	Ambalaj Packing (mt)
3	7/64"	6	1,5	15	low pressure	6 bar	50 mt
4	5/32"	7	1,5	20	low pressure	6 bar	50 mt
5	3/16"	8	1,5	30	low pressure	6 bar	50 mt
6	¼"	10	2,0	40	low pressure	6 bar	50 mt
7	9/32"	11	2,0	40	low pressure	6 bar	50 mt
8	5/16"	12	2,0	50	low pressure	6 bar	50 mt
9	23/64"	13	2,0	60	low pressure	6 bar	50 mt
10	3/8"	15	2,5	70	low pressure	6 bar	50 mt
11	7/16"	17	3,0	80	low pressure	6 bar	50 mt
12	½"	18	3,0	80	low pressure	6 bar	25 mt
13	½"	20	3,5	100	low pressure	6 bar	25 mt
14	35/64"	21	3,5	100	low pressure	6 bar	25 mt
15	35/64"	23	4,0	100	low pressure	6 bar	25 mt
16	5/8"	24	4,0	125	low pressure	6 bar	25 mt
18	11/16"	26	4,0	150	low pressure	6 bar	25 mt
19	11/16"	27	4,0	190	low pressure	6 bar	25 mt
20	½"	28	4,0	190	low pressure	6 bar	25 mt

NOT : Diğer ölçü,markalama ve ambalaj gibi ürün özellikleri müşterinin isteği üzerine değişiklik gösterebilir.

NOTE : Other dimensions,marking and packaging vary upon customer's request

Markalama / Marking : WINLAS DIN 73411-C- ID / OD >EPDM< LOT DATE